



## Origin™ 200

### Scalable Multiprocessing Server with an Industry-Leading Combination of Price/Performance, I/O Bandwidth, RAS, and Investment Protection

Sharing and delivering information simply and seamlessly, when and where it is needed, are essential to business success. The fundamental nature of information exchange is changing radically—constantly accelerating in immediacy, diversity, and density. With UNIX® tools and performance, scalability in all dimensions, interoperability services, and an entry price comparable to PC-based servers, Origin 200 makes perfect business sense.

### Grows as Your Business Grows

Modular in design, Origin 200 allows you to pay only for what you need now—with no additional cost for unused potential. Unlike other symmetric multiprocessing (SMP) servers that accommodate additional processors without growing I/O bandwidth, the Origin 200 NUMA architecture adds bandwidth and slot capacity by adding a second tower. Like typical SMPs, however, Origin 200 uses a simple shared-memory programming model provided by the NUMalink™ interconnect, which extends shared memory between two towers.

### Quick and Easy Integration and Administration

Origin 200 is easy to set up and administer and includes comprehensive software tools to guide the initial setup and configuration tasks. From initial login, SGI™ Internet Gateway software guides you through networking and file setup tasks and makes it possible to interact with and administer the server through a Web browser from any system on your intranet.

### Out-of-the-Box Productivity

SGI supports a broad spectrum of complete prepackaged solutions for Origin 200 designed to deliver immediate productivity and empower your business. Application areas such as file serving, Internet serving, media streaming, high availability, image rendering, and scientific or technical computing have optimized available hardware and software packages. Origin solution templates allow you to capitalize on field-tested success and show immediate results by eliminating configuration guesswork.

### Seamless Interoperability for a Multiplatform Environment

With interoperability support for PC and Macintosh® filesystems, Origin 200 fits seamlessly into your multiplatform computing environment. Network integration is accomplished easily through the use of optional Windows®, NetWare™, Samba, and AppleShare® services.

### Reliability, Availability, and Serviceability—Critical to Your Success

Resilient to failure, Origin 200 features embedded environmental sensors and a system controller that manages power and cooling systems locally or to a remote location. The addition of the optional IRIS FailSafe™ software provides failover capability between two servers to ensure uninterrupted availability for your critical enterprise applications. Origin 200 servers feature ECC memory and cache, dual SCSI controllers, hot-pluggable drives, and optional redundant power configurations to ensure that your uptime is maximized.





## Origin 200 Technical Specifications

<b>Processor Data</b> <ul style="list-style-type: none"> <li>Microprocessor: 64-bit MIPS® RISC R10000® 360 MHz 64-bit MIPS RISC R12000™ 270 MHz</li> <li>Primary caches: 32KB two-way set-associative on-chip instruction cache 32KB two-way set-associative on-chip data cache</li> <li>Secondary cache: 360 MHz: 4MB ECC cache/processor 270 MHz: 4MB ECC cache/processor</li> </ul>	<b>Mass Storage</b> <ul style="list-style-type: none"> <li>Interfaces: Ultra SCSI and Fibre Channel</li> <li>Maximum bandwidth: 40MB/sec Ultra SCSI, 100MB/sec Fibre Channel</li> <li>Device capacity: Ultra SCSI: 9.1GB, 18.2GB, Fibre Channel: 9.1GB, 18.2GB, 36 GB</li> <li>Tape: 4 mm DDS4,DLT</li> <li>CD-ROM: 40x internal</li> <li>Fibre Channel: SGI™ TP9100, 12 x 3.5" devices TP9100, Up to nine TP9100s per rack</li> <li>RAID: (108 drives, 18GB, 36GB, 73GB) 11.9TB dual tower [Ultra SCSI] 67.3TB dual tower [Fibre Channel] 265TB dual tower [Fibre Channel RAID]</li> </ul>	<b>Dimensions and Weights</b> <ul style="list-style-type: none"> <li>Tower dimensions: 23" H, 26.5" D, 9" W [58.4 cm H, 67.3 cm D, 22.8 cm W]</li> <li>Rack-mountable: 19" customer supplied rack or SGI rack</li> <li>Rack-mounted dimensions: 6.8" H, 25" D, 17.4" W [17.3 cm H, 63.5 cm D, 44.2 cm W]</li> <li>Weight: 59 lb [27 kg] minimum</li> </ul>																																																
<b>Single-Tower Configuration</b> <ul style="list-style-type: none"> <li>CPU capacity: 1 to 2 R10000 or R12000 CPUs per tower</li> <li>Memory capacity: 256MB to 2GB ECC protected</li> <li>Cache coherency: Fully in hardware</li> <li>Interleaving: 4-way per bank</li> <li>I/O bandwidth: 1.15GB/sec sustained, 1.44GB/sec peak</li> <li>Memory bandwidth: 630MB/sec sustained, 720MB/sec peak</li> <li>I/O slots: 3 full-size 32/64-bit 33 MHz 3.3/5 V PCI, 200MB/sec sustained</li> <li>Internal storage channels: 5 XIO, 7 PCI slots with GIGACHannel™</li> <li>Storage capacity: 1 40MB/sec Fast/Wide Ultra SCSI and 1 20MB/sec Fast/Narrow Ultra SCSI</li> <li>Storage capacity: 6 3.5" fixed media hot-pluggable drive bays, 2 5.25" removable media drive bays</li> <li>Communication: 1 10Base-T/100Base-TX, 2 460Kb/sec serial ports, 1 parallel port</li> <li>Cooling: 3 variable-speed fans</li> </ul> <p>Dual-tower system also available</p>	<b>Software</b> <ul style="list-style-type: none"> <li>System: IRIX® 6.5 ASE, X/OPEN XPG4 BASE 95, IEEE POSIX 1003.2, and 1003.1b, 1003.1c FIPS 151-2, UNIX® System V.4, 4.3 BSD extensions, MIPSABI, SVID issue 3, X11R6, Motif™ Window Manager 1.2, IRIS GL™, OpenGL®</li> <li>Networking: TCP/IP, NFS™ V2/V3, RSVP, DHCP, Bulk Data Service [BDSpro], NetVisualizer™</li> <li>Server: XFS™ 64-bit journaled filesystem with guaranteed rate I/O, system MIB [Provision], software distribution</li> <li>Web server: Netscape® Enterprise server, Netscape FastTrack Web server, SGI Internet Gateway</li> <li>Propel: IRIS NetWorker, IRIXPro™ Systems Management Toolbox, Performance Co-Pilot™ system and network performance monitoring software</li> <li>Compilers: ANSI C, C++, Fortran 77, Ada, Pascal, Power C Accelerator [PCA], Power Fortran 77, Fortran 90, Power Fortran 90</li> <li>PC/Macintosh Integration: Syntax TotalNET Advanced Server [TAS], supports Windows® 95 and Windows NT® [SMB], NetWare, AppleShare, Samba for IRIX</li> <li>Security: Trusted IRIX™ version 6.x with BI security, Commercial Security Pack [CSP]</li> <li>High availability: IRIS FailSafe [optional]</li> </ul>	<b>Environmental [Nonoperating]</b> <ul style="list-style-type: none"> <li>Temperature: -20° to +60° C</li> <li>Humidity: 10% to 95% noncondensing</li> <li>Altitude: 40,000 MSL</li> </ul> <b>Environmental [Operating]</b> <ul style="list-style-type: none"> <li>Temperature: +5° to +35° C</li> <li>Humidity: 10% to 80% noncondensing</li> <li>Altitude: 10,000 MSL</li> <li>Noise: 55 dBA</li> </ul> <b>Electrical and Power</b> <ul style="list-style-type: none"> <li>Voltage: 110/220 VAC 1 Phase auto-sensing worldwide power supply</li> <li>Power supply: Standard 483 W, Optional Redundant Power Supply [RPS]</li> <li>Frequency: 50/60 Hz</li> <li>Heat dissipation: 2,300 BTU/hr, maximum</li> <li>Electrical service: 100/110 VAC @ 15A, 200/220 VAC @ 10A U.S., Japan, NEMA 5-15 P [110 V], 6-15P [220 V]</li> </ul>																																																
<b>GIGACHannel</b> <ul style="list-style-type: none"> <li>Bus type: XIO, PCI</li> <li>XIO: Additional 5 slots</li> <li>XIO bandwidth: 1.15GB/sec sustained, 1.44GB/sec peak</li> <li>PCI: Additional 4 slots</li> <li>PCI bandwidth: 200MB/sec sustained, 267MB/sec peak</li> </ul>		<b>Regulatory</b> Origin 200 is classified FCC Class A, CE, CSA, TUV, UL, CISPR A, and VCCI Class 2 certified																																																
<b>PCI Options</b> Fast/Wide Ultra SCSI differential, Fast/Wide Ultra SCSI single-ended, 10Base-T/100Base-TX ethernet, FDDI dual attach, Fibre Channel, 8-port audio, Gigabit Ethernet, OC3, OC12		<b>Configuration Summary</b> <table border="1"> <thead> <tr> <th></th> <th>Single-tower Origin 200</th> <th>Dual-tower Origin 200</th> </tr> </thead> <tbody> <tr> <td>R12000 Physical memory, MB ECC</td> <td>1 to 2 256 to 2048</td> <td>2 to 4 512 to 4096</td> </tr> <tr> <td>Disk capacity, internal</td> <td>216GB</td> <td>432GB</td> </tr> <tr> <td><b>Standard I/O</b></td> <td></td> <td></td> </tr> <tr> <td>5.25" bays</td> <td>2</td> <td>4</td> </tr> <tr> <td>3.5" hot plug bays</td> <td>6</td> <td>12</td> </tr> <tr> <td><b>Base I/O</b></td> <td></td> <td></td> </tr> <tr> <td>Serial ports</td> <td>2</td> <td>4</td> </tr> <tr> <td>Parallel ports</td> <td>1</td> <td>2</td> </tr> <tr> <td>10Base-T/100Base-TX ethernet</td> <td>1</td> <td>2</td> </tr> <tr> <td>Internal Fast/Wide Ultra SCSI, 40MB/sec</td> <td>1</td> <td>2</td> </tr> <tr> <td>Internal Fast/Narrow Ultra SCSI, 20MB/sec</td> <td>1</td> <td>2</td> </tr> <tr> <td>PCI 32/64-bit slots standard</td> <td>3</td> <td>6</td> </tr> <tr> <td><b>GIGACHannel</b></td> <td></td> <td></td> </tr> <tr> <td>PCI slots</td> <td>7</td> <td>10/14*</td> </tr> <tr> <td>XIO slots</td> <td>5</td> <td>5/10*</td> </tr> </tbody> </table> <p>*Origin 200 GIGACHannel</p>		Single-tower Origin 200	Dual-tower Origin 200	R12000 Physical memory, MB ECC	1 to 2 256 to 2048	2 to 4 512 to 4096	Disk capacity, internal	216GB	432GB	<b>Standard I/O</b>			5.25" bays	2	4	3.5" hot plug bays	6	12	<b>Base I/O</b>			Serial ports	2	4	Parallel ports	1	2	10Base-T/100Base-TX ethernet	1	2	Internal Fast/Wide Ultra SCSI, 40MB/sec	1	2	Internal Fast/Narrow Ultra SCSI, 20MB/sec	1	2	PCI 32/64-bit slots standard	3	6	<b>GIGACHannel</b>			PCI slots	7	10/14*	XIO slots	5	5/10*
	Single-tower Origin 200	Dual-tower Origin 200																																																
R12000 Physical memory, MB ECC	1 to 2 256 to 2048	2 to 4 512 to 4096																																																
Disk capacity, internal	216GB	432GB																																																
<b>Standard I/O</b>																																																		
5.25" bays	2	4																																																
3.5" hot plug bays	6	12																																																
<b>Base I/O</b>																																																		
Serial ports	2	4																																																
Parallel ports	1	2																																																
10Base-T/100Base-TX ethernet	1	2																																																
Internal Fast/Wide Ultra SCSI, 40MB/sec	1	2																																																
Internal Fast/Narrow Ultra SCSI, 20MB/sec	1	2																																																
PCI 32/64-bit slots standard	3	6																																																
<b>GIGACHannel</b>																																																		
PCI slots	7	10/14*																																																
XIO slots	5	5/10*																																																
<b>XIO Option Cards</b> 4-port Ultra SCSI, 1-port Fibre Channel [copper or fiber], 4-port 100Base-TX with 6 460Kb/sec serial ports, 4-port ATM OC3, HIPPI serial [200MB/sec full duplex], 6U and 9U VME, DIVO, GSN, FDDI dual attach	<b>Support and Warranty</b> One-year hardware warranty with advanced parts exchange; remote diagnostics support available																																																	



**Corporate Office**  
1600 Amphitheatre Pkwy.  
Mountain View, CA 94043  
[650] 960-1980  
www.sgi.com

North America [800] 800-7441  
Latin America [650] 933-4637  
Europe [44] 118.925.75.00  
Japan [81] 3.5488.1811  
Asia Pacific [65] 771.0290