

SGI Internet Server™

Features and Benefits

- · Low entry cost
- Thin [2U] form factor for more units per rack
- · Reliable Linux operating system
- Preinstalled, fully supported tools for quick deployment, easy monitoring, and remote administration
- Web-based tools to streamline installation, troubleshooting, and networking
- · Security lockdown and intrusion detection software
- High-performance integrated basic services for Web serving and messaging
- Preinstalled Apache Web Server plus SGI performance enhancements
- Single-point-of-call support with world-class SGI global services and support

The final Price Continues Continues

The Fast and Easy Way to Deploy Internet Server Solutions

The server company that powers the world's most demanding Web sites now offers a powerful thin server for the Internet. SGI Internet Server combines the convenience of an appliance with the flexibility of an open system.

Designed for ISPs, ASPs, and colocation facilities, the Linux® OS-based SGI Internet Server is a cost-effective, completely integrated, thin serving solution, which provides quick installation and deployment for these high-growth environments. SGI Internet Server includes advanced management, monitoring, and security tools with integrated basic services for Web serving and messaging.

SGI Internet Server provides a foundation to support the entire suite of applications found in high-volume environments of service providers, such as high-volume messaging services, large Web-hosting applications, e-commerce applications, and media-serving applications.

Designed to Grow with Your Business

To meet ever-increasing customer demands, service providers must have the ability to integrate new solutions into existing infrastructures quickly and affordably. The entry-level priced SGI Internet Server is designed specifically for service providers that need to keep pace with expanding network needs while controlling expenses.

In addition to delivering optimum reliability, SGI Internet Server offers simple rack-and-stack scalability. Service providers can expand their services with minimal hassle and expense. Adding shared Web hosting servers or more messaging capacity is as simple as stacking an additional SGI Internet Server into the rack.

Internet service providers must also factor space limitations into their product selection decisions and get exceptional performance in the smallest package possible. SGI Internet Server is as powerful as it is compact. With up to 19 dual-processor SGI Internet Servers installed in a full-height rack, service providers have a powerful solution to handle extremely high-volume Internet serving requirements.

Reduced Support Costs Increase the Bottom Line

SGI Internet Server is highly reliable, requires very little maintenance or support, and integrates advanced manageability features. Support costs are further reduced due to:

- · A reliable Linux platform
- · Centralized configuration, administration, and management
- Improved system security through integrated server lockdown tools SGI also reduces support costs by offering complete single-point-of-call support for hardware and software issues, providing a quick response from the world-class SGI global services and support organization.

Reliable Thin Server Architecture

SGI Internet Server is based on the SGI™ 1200 server, which combines SGI's commitment to high-performance, scalable servers with the reduced cost and reliability of the Linux operating system. Leveraging SGI's collaborative development with the open source community, SGI Internet Server is optimized to provide high performance for the Linux operating system.

Turn to SGI for More Affordable Internet Server Solutions

SGI Internet Server is the most viable solution for service providers interested in taking advantage of the reliability of the Linux operating system. The solution is delivered in a small form factor and allows service providers to expand their value-added services and scale to meet the needs of their customers with the highest degree of cost-efficiency.

SGI Internet Server is part of the SGI Media Commerce™ solutions suite of products that enable customers to transact content over a vast range of network types.

SGI Internet Server Features and Specifications

Manageability Features

Centralized Management

- · Configuration and administration of a single server or a cluster of servers
- · Easy-to-use Web-based user interface, central repository, one-stop configuration and customization

Performance Co-Pilot[™] Performance Monitoring Tool

- ·Improve uptime and reliability of your service
- · Effectively and accurately bill customers for usage

Customer Content Management

- End users can easily upload information using FTP
 Improve customer self-service and reduce the need for technical support

Security Features

Intrusion Detection

· Tripwire Integrity Assessment Technology actively monitors configuration files to safeguard against corruption or tampering

•The integrated Bastille Hardening Program provides lockdown scripts and a secure configuration that protects against unauthorized use

SGI Secure Server Operations Guide

· A guide to help make security-conscious customization and operations

Applications

- Preinstalled Apache Web Server plus SGI performance
- · Preinstalled SendMail messaging services

SGI Internet Server Hardware Specifications

Dimensions and Weights

3.5" (2U) x 19" x 25.25" Rack-mount

8.89 cm x 48.26 cm x 64.14 cm 45 lb minimum configuration [or 20.41 kg] Weight

Shipping weight 70 lb [or 31.75 kg] maximum, including

packaging and documentation

Operating System Support

Red Hat® Linux, SGI ProPack for Linux'

For most current list, see www.sgi.com/software/linux/tech_info.html

Processor Support

Microprocessor Intel® Pentium® III CPU 1-2 CPUs · CPU capacity

· Clock speed 700 MHz or higher

32KB [16KB data/16KB instruction] nonblocking · Primary caches · Advanced transfer 256KB unified, nonblocking, full-speed on-die

System Memory

Memory capacity Up to 2GB SDRAM, ECC protected

·Memory bandwidth 800MB/sec

System Features

System bus speed 100 MHz

·I/O bandwidth 133MB/sec [or 1064Mb/sec] peak · RAS features Remote management port

Hot pluggable internal drives · Cooling

Two fans for hard drive bay One fan for the power supply

Heat sink fans on CPU · Keyboard/mouse 2 PS/2, 8240A compatible

port Serial ports 2 asynch, RS-232C, 9-pin

1 IEEE 1284, 25-pin bidirectional · Parallel port

Networking and Storage CD-ROM drive 32X max. speed ATAPI CD-ROM drive preinstalled

3.5" x 1.0" 1.44MB floppy disk drive preinstalled · Floppy drive One 32-bit Peer PCI channel running at 33 MHz · I/O channels

·I/O slots 2 PCI slots

1 LVDS SCSI channel · Internal storage

4 Ultra2 SCSI hot swap drive bays capacity · Ethernet port 1 10/100Mb/sec auto-switch Ethernet port

[Intel 82c559]

Single-ended Ultra SCSI, 68-pin · External SCSI

Support and Warranty

upgrades

Three-year hardware warranty, year one Warranty

with next-business-day response, years

two and three parts-only

· Software support 90 days advisory support [business hours] · Hardware support Upgrades available for same day and up to

7x24 on-site response

Upgrades available from limited-incident · Software support packages up to 7x24 annual contracts upgrades

Environmental and Regulatory Environmental -40°C to +70°C

[nonoperating]

Environmental +10°C to +35°C

(operating)

· Electrical and 115 V/60 Hz; 230 V/50 Hz

power Regulatory Meets or exceeds following requirements: UL 1950, 3rd Edition (UL and cUL) -U.S./Canada

-Europe/CE Mark EN 60 950, German GS Mark to

EN 60 950

-International Certified by NEMKO to meet

requirements of EN 60 950 with amendments and Nordic deviations and IEC 950 with amendments

Electromagnetic compatibility [EMC]

FCC CFR 47 Part 15 Class A

-Canada Complies with limits for radio noise

emissions for Class A digital apparatus

as required by Industry Canada [IC]
-Europe/CE Mark EN55022 and EN50082-2 [CE Mark complies with EU EMC Directive

89/336/EECI

-International CISPR 22, Class A -Japan

VDDI, Class 2 [based on CISPR 22 requirements

Hardware Scalability

2U rack-mountable SGI Internet Server

Up to 19 servers in a full rack configuration

· Up to 1.152TB of internal storage in a full rack configuration

112057

· Optional hardware upgrades are available to increase

memory, CPU, or storage as required

For more information please visit: www.sai.com/ao/broadband



Corporate Office 1600 Amphitheatre Pkwy. Mountain View, CA 94043 [650] 960-1980

www.sgi.com

2634 [10/00]

North America 1[800] 800-7441 Latin America 1[650] 933-4637 Europe [44] 118,925,75,00 Japan (81) 3.5488.1811 Asia Pacific [65] 771.0290

© 2000 Silicon Graphics, Inc. All rights reserved. Specifications subject to change without notice. SGI, Media Commerce, SGI Media Commerce, Performance Co-Pilot, SGI Internet Server, and the SGI logo are trademarks of Silicon Graphics, Inc. SGI ProPack for Linux is a trademark of Silicon Graphics, Inc., used by permission. Intel and Pentium are registered trademarks of Intel Corporation. Linux is a registered trademark of Linux Torvalow. Microsoft, Windows, and Windows NT are registered trademarks of Microsoft Corporation. Red Hat is a registered trademark of Red Hat, Inc. All other trademarks mentioned herein are the property of their respective owners.