

# SGI UV 2000, UV 30: Big Brains for No-Limit Computing

The Most Powerful In-memory Supercomputers for  
Compute-Intensive Workloads

## Key Features

Scales up to 256 sockets and  
64TB of coherent shared memory

SMP System utilizes  
industry-standard Intel® Xeon®  
processors and Linux® O/S

Builds on 20 years of in-memory  
computing expertise



## Solve the Most Demanding Compute-Intensive Problems

Part of the SGI UV server line for high performance in-memory computing, SGI UV 2000 and SGI UV 30 are advanced symmetric multiprocessing (SMP) systems designed for compute-intensive, fast algorithm workloads such as CAE, CFD, and scientific simulations.

SGI UV 2000 scales to truly extraordinary levels—up to 256 CPU sockets and 64TB of cache-coherent shared memory in a single system. Enabling such powerful in-memory computing capability is 6th generation SGI NUMalink® ASIC technology, providing extreme bandwidth, low latency network interconnects. Equipped with an integrated MPI Offload Engine, UV 2000 can also be leveraged for distributed applications and as a “super node” for clustered high performance computing (HPC) systems.

Designed for smaller, compute-intensive environments, SGI UV 30 is a 2U, 4-socket server providing up to 1.5TB of in-memory computing power.

## Single System Simplicity with Extreme Scalability

The SGI UV 2000 features a modular chassis design that enables users to grow their system without adding complexity. A 10U chassis contains up to 16 sockets and 24 threads coupled with an All-to-All NUMalink network topology. By adding additional chassis (up to four per standard 19” rack) and using an Enhanced Hypercube topology, UV 2000 can scale up to 256 sockets and

4,096 threads, all operating as a single system. It's like running a giant workstation with lightning speed and maximum investment protection.

## Flexible, Open, Energy Efficient

SGI UV 2000 is designed with optimum flexibility. Featuring Intel® Xeon® E5-4600 processors with eight DIMMs per socket, the system's x86 architecture delivers a high processor to memory ratio. NVIDIA® Quadro® and NVIDIA® Tesla® GPU accelerators and Intel® Xeon® Phi™ coprocessors can also be added. A choice of unmodified SUSE® Linux® Enterprise Server or Red Hat® Enterprise Linux operating systems make the UV 2000 ideal for standard ISV and open source applications as well custom codes. And SGI's innovative air or water cooling helps lower energy costs.

## High Performance Storage with Fast Access

Industry-standard PCIe Gen3 expansion slots provide countless options for persistent storage with fast I/O, very-high bandwidth connectivity. For hardware, select from the entire SGI InfiniteStorage line of Storage Servers, RAID and tape libraries, as well as industry-standard 3rd party components. For storage software, leverage Intel® Enterprise Edition for Lustre, SGI CXFS™, or industry standard XFS® file systems, SGI XVM® volume management, SGI DMF™ tiered data management, and 3rd party backup solutions.



## UV 2000, UV 30 Configuration Specifications

sgi.com/uv

<b>SGI UV 2000 System Components</b>	
<b>Processors</b>	<ul style="list-style-type: none"> <li>Intel® Xeon® processor E5-4600 v2 product family (2.4-3.3GHz)</li> </ul>
<b>Memory</b>	<ul style="list-style-type: none"> <li>8, 16 or 32GB up to 1600 MT/s ECC DDR3 DIMMs</li> </ul>
<b>Disk Drives</b>	<ul style="list-style-type: none"> <li>2.5" SATA, SAS HDD or SSD</li> </ul>
<b>Interconnect</b>	<ul style="list-style-type: none"> <li>NUMalink® 6 (NL6; 6.7GB/s bidirectional)</li> </ul>
<b>Environmental</b>	<ul style="list-style-type: none"> <li>68-77F (20-25C), 40-55% relative humidity (non-condensing)</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>Single phase 30 amp or three phase (208, 400 or 480VAC) 60 amp</li> </ul>
<b>Cooling</b>	<ul style="list-style-type: none"> <li>Ambient air-cooled</li> <li>Optional water-cooled: water temp. 45-60F (7.2-15.6C)</li> </ul>
<b>Rack</b>	
<b>SGI Rack Dimensions (H x W x D)</b>	<ul style="list-style-type: none"> <li>79.5" (42U) x 31.3" x 46.2"</li> <li>201.9cm x 79.5cm x 117.3cm</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>Single-phase 180-264VAC or three-phase 180-504VAC, 47-63Hz</li> </ul>
<b>Cooling</b>	<ul style="list-style-type: none"> <li>Open-looped airflow or optional water-cooled door</li> </ul>
<b>3rd party rack</b>	<ul style="list-style-type: none"> <li>Supported for UV 2000 configurations up to one rack scale</li> </ul>
<b>Blade Enclosure</b>	
<b>Dimensions (H x W x D)</b>	<ul style="list-style-type: none"> <li>17.5" (10U) x 19" x 27"</li> <li>44.5cm x 48.36cm x 68.68cm</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>Three 12VDC 3037W, 200-240VAC or 277VAC input voltage (N+1)</li> </ul>
<b>Cooling</b>	<ul style="list-style-type: none"> <li>Nine hot-pluggable, 119mm, 12VDC axial cooling fans</li> </ul>
<b>Administrative Network</b>	<ul style="list-style-type: none"> <li>One Chassis Management Controller</li> <li>Two backplane connections</li> </ul>
<b>Compute Blade</b>	
<b>Dimensions (H x W x D)</b>	<ul style="list-style-type: none"> <li>3.7" x 8.4" x 18.1"</li> <li>9.4cm x 2.1cm x 46.0cm</li> </ul>
<b>2 CPU CPU + Accelerator</b>	<ul style="list-style-type: none"> <li>2 Intel® Xeon® processor E5-4600 product family</li> <li>1 Intel® Xeon® processor E5-4600 product family and 1 accelerator card</li> </ul>
<b>Memory</b>	<ul style="list-style-type: none"> <li>8 DIMM Slots per Intel® Xeon® CPU</li> </ul>
<b>IO expansion options</b>	<p>All IO slots are X16 Gen 3 capable. Options per blade include:</p> <ul style="list-style-type: none"> <li>Base IO (specs below)</li> <li>Two 2.5" HDD or SSD slots</li> <li>Two low-profile slots</li> <li>One low-profile and one full-height, half-depth slot</li> </ul>
<b>Base I/O Features</b>	<ul style="list-style-type: none"> <li>Two 1.8" SATA SSD slots</li> <li>3.0GB/s SAS controller with two X4 ports</li> <li>Two USB 2.0 ports</li> <li>Serial port</li> <li>VGA port</li> <li>Two Ethernet ports</li> <li>Dedicated Board Management Controller</li> </ul>
<b>System Expansion and Enhancement Options</b>	
<b>Large, Multi-partition UV2000 systems</b>	<ul style="list-style-type: none"> <li>NUMalink 6 support for up to 16,384 socket system</li> <li>Support for Shared Memory up to 8 Petabytes</li> <li>Hard partitions maintain resilience while offering management flexibility</li> </ul>
<b>Graphics and Coprocessors</b>	<ul style="list-style-type: none"> <li>NVIDIA® Quadro® 5000/5200/6000 and NVIDIA® Tesla® K20x/K40 GPU computing accelerator</li> <li>Intel® Xeon® Phi™ coprocessor</li> <li>Scales to 32 accelerator devices within a single system image</li> </ul>

Global Sales and Support: [sgi.com/global](http://sgi.com/global)

©2015 Silicon Graphics International Corp. All rights reserved. SGI, UV, ICE, NUMalink, CXFS, XFS, DMF, XVM and the SGI logo are registered trademarks or trademarks of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries. Intel, Xeon and the Intel Xeon logo are registered trademarks of Intel Corporation. All other trademarks are properties of their respective holders. 15042013 4377 04062015

<b>UV 2000 System Management</b>	
<b>Board Management Controller</b>	<ul style="list-style-type: none"> <li>One per compute blade</li> <li>Monitors blade function</li> <li>Relays status or function data to management network</li> </ul>
<b>Chassis Management Controller</b>	<ul style="list-style-type: none"> <li>One per blade enclosure</li> <li>Controls master power to all compute blades</li> <li>Monitors power and blade enclosure environment</li> </ul>
<b>System Management Node</b>	<ul style="list-style-type: none"> <li>One per system</li> <li>Monitors and controls power and environmentals</li> <li>Manages hardware inventory and configuration, reports health status and failure analysis</li> </ul>
<b>SGI UV 30 4-way Server Specifications</b>	
<b>CPU</b>	<ul style="list-style-type: none"> <li>4 Intel® Xeon® processor E5-4600 v3 product family 6, 10, 12 or 16 core CPU's, 2.0-2.9 GHz</li> </ul>
<b>Memory</b>	<ul style="list-style-type: none"> <li>Up to 48 DIMM slots</li> <li>8, 16, or 32GB 2133 MT/s ECC DDR4 DIMMs</li> </ul>
<b>Storage</b>	<ul style="list-style-type: none"> <li>Up to 20 2.5" SAS3 HDD/SSD plus 4 2.5" NVME</li> </ul>
<b>IO Expansion</b>	<ul style="list-style-type: none"> <li>2 PCIe3x16 FHFL; 2x8 FHFL; 4x8 internal; GPUs reduce PCIe</li> </ul>
<b>High End PCI</b>	<ul style="list-style-type: none"> <li>Up to 2 NVIDIA® Quadro®, NVIDIA® Tesla® computing accelerators or 2 Intel® Xeon® Phi™ Coprocessors</li> </ul>
<b>Dimensions</b>	<ul style="list-style-type: none"> <li>2U, 17.2" (437mm) x 33.81" (859mm) x 3.5" (89mm)</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>2 2000W redundant power supplies; 110/220V</li> </ul>
<b>Cooling</b>	<ul style="list-style-type: none"> <li>4 8cm fans</li> </ul>
<b>Other</b>	<ul style="list-style-type: none"> <li>Base system includes BMC with remote management, 4x1GB LAN</li> </ul>
<b>Storage</b>	
<b>SGI InfiniteStorage™ Solutions</b>	<ul style="list-style-type: none"> <li>SGI RAID, NAS, SAN, Storage Servers, MAID and tape libraries</li> </ul>
<b>SGI InfiniteStorage Software</b>	<ul style="list-style-type: none"> <li>CXFS™, XFS®, DMF™, XVM®, and backup and restore solutions</li> </ul>
<b>Software Development</b>	
<b>Programming Languages and Debuggers</b>	<ul style="list-style-type: none"> <li>SGI Development Suite</li> <li>C &amp; C++: Intel® C++ Compiler, GNU GCC</li> <li>Debuggers: Intel® Debugger included with Intel® compilers, GNU GDB, Rogue Wave Software® TotalView®, Allinea DDT</li> <li>Fortran: Intel® Fortran Compilers, GNU GCC</li> <li>Performance Analysis: Intel® VTune Amplifier XE, Intel® Trace Analyzer &amp; Collector</li> </ul>
<b>Libraries</b>	<ul style="list-style-type: none"> <li>SGI MPI</li> <li>OpenMP included with Intel® compilers</li> <li>Intel® Math Kernel Library</li> <li>Intel® Parallel Building Blocks</li> <li>Intel® Integrated Performance Primitives</li> <li>Intel® MPI Library</li> </ul>
<b>System Software</b>	
<b>Operating Systems</b>	<ul style="list-style-type: none"> <li>SUSE® Linux® Enterprise Server 11</li> <li>Red Hat® Enterprise Linux 6</li> </ul>
<b>SGI Linux System Software</b>	<ul style="list-style-type: none"> <li>SGI Foundation Software</li> <li>SGI Performance Suite</li> <li>SGI Management Suite</li> </ul>
<b>Virtualization Software</b>	<ul style="list-style-type: none"> <li>KVM</li> </ul>

## About SGI

SGI is a global leader in high performance solutions for compute, data analytics and data management that enable customers to accelerate time to discovery, innovation, and profitability. Visit [sgi.com](http://sgi.com) for more information.

